



## DECLARATION OF PERFORMANCE No. 0208

1. Unique identification code of the product-type: **BIOFLEX – EN 12004 – C2 TE**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**The batch number is printed on the packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Improved cementitious adhesive for ceramic tiling, all internal and external tiling**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3 and System 3 for reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

**The notified testing laboratory Modena Centro Prove No. 1599 performed the determination of the product-type on the basis of type testing on samples taken by the manufacturer, under system 3, and issued the test report No. 20134521/1 del 19/09/2013 + 20134521/2 del 19/09/2013 + 20134521/3 del 19/09/2013**

**The notified testing laboratory Istituto Giordano No. 0407 performed the determination of the reaction to fire on samples taken by the manufacturer, under system 3, and issued the classification report No. 293410/6862/CPD, 293409/6861/CPD**

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**

9. Declared performance :

Essential characteristics	Performance	Harmonized technical specification
<b>Reaction to fire</b>	<b>Class A1/A1<sub>fl</sub></b>	<b>EN 12004:2007 + A1:2012</b>
<b>Bond strength as: initial tensile adhesion strength</b>	<b>≥ 1,0 N/mm<sup>2</sup></b>	
<b>Durability for: Tensile adhesion strenght after heat ageing Tensile adhesion strenght after water immersion Tensile adhesion strenght after freeze-thaw cycles</b>	<b>≥ 1,0 N/mm<sup>2</sup> ≥ 1,0 N/mm<sup>2</sup> ≥ 1,0 N/mm<sup>2</sup></b>	
<b>Release of dangerous substances</b>	<b>See SDS</b>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4..

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

Sassuolo 28/10/2013

[www.kerakoll.com](http://www.kerakoll.com)