

DECLARATION OF PERFORMANCE

No.01DCG20130612

1. Description of Product:
Dura Casa Group

Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

**Akgün Seramik Tic ve A.Ş. İçerenköy mah. No:16 Kutay İş Merkezi C Blok Kat:3
Ataşehir/İstanbul/TÜRKİYE**

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

5. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness:		
ISO 10545-17 (Dynamic Coefficient of Friction)	≥ 0,60μ	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

İsmail BEKTAŞ R&D Chief

Name and function

18 June 2013

Place and date of issue

AKGÜN
SERAMİK
AKGÜN SERAMİK SANAYİ VE TİCARET A.Ş.
Mrk : Tankpalet Fab. Karş. Ford Plaza Üzeri ADAPAZARI
Tel.: 0 264 276 72 10 (5 Hat) Fax: 0 264 276 72 16
İrt. Büro: Değirmen Yolu Sk. No: 16 Kutay İş Merkezi C Blok Kat: 3
İçerenköy / İSTANBUL Tel: (0 216) 574 88 40 Fax: (0 216) 574 88 46
A. Fuat Cebesoy V.D. 025 005 1808

Signature